

Application / Specification Data for Tungsten ToolWorks' Series End Mills



Peripheral Milling data based on axial depth \leq 100% of tool diameter & radial depth of \leq 25% of tool diameter.



Slot Milling data based on axial depth of cut = 50% of tool diameter.

The milling data presented below is for all "standard" Series of TTW end mills (data is presented separately on each respective product page for our application-specific high performance designs).
 Note: When using SmoothCoat & SmoothEdge surface treatments, Surface Feet or Meters Per Minute can be increased from the stated levels by at least 25%.

Material	SFPM		1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	5/8"	3/4"	1"
	Peripheral	Slotting	Feed Per Tooth (FPT)									
Steel												
1018 / 1020	150 to 350	150 to 300	.0005	.0010	.0015	.0018	.0020	.0025	.0030	.0035	.0040	.0045
4140 / 4340 / P20	150 to 300	125 to 225	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0025	.0030	.0040
Stainless Steel												
303 / 304 / 316	150 to 300	125 to 250	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0030	.0040	.0040
410 / 420 / 440C	150 to 300	125 to 250	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0025	.0035	.0038
15-5/17-4 \leq 32HRc	125 to 250	100 to 225	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0025	.0030	.0038
15-5/17-4 \geq 32HRc	100 to 150	100 to 150	.0003	.0005	.0010	.0012	.0015	.0015	.0015	.0020	.0030	.0038
13-8 / 316L	125 to 300	125 to 250	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0030	.0040	.0040
Tool Steel												
A2/D2/H13 \leq 32HRc	125 to 250	100 to 200	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0025	.0030	.0035
A2/D2/H13 \geq 32HRc	100 to 150	100 to 125	.0003	.0005	.0010	.0012	.0015	.0015	.0015	.0020	.0030	.0035
Titanium												
6Al-4V	120 to 250	100 to 175	.0005	.0007	.0010	.0012	.0012	.0018	.0020	.0020	.0030	.0040
High Temp Alloys												
Inconel 625	50 to 150	50 to 125	.0005	.0007	.0010	.0012	.0012	.0018	.0020	.0020	.0025	.0030
Inconel 718	50 to 150	50 to 125	.0003	.0005	.0010	.0012	.0012	.0015	.0015	.0020	.0025	.0025
Cast Iron												
Gray Iron \leq 32HRc	150 to 350	125 to 300	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0030	.0040	.0045
Ductile Iron	150 to 300	125 to 250	.0005	.0007	.0010	.0012	.0015	.0018	.0020	.0025	.0035	.0045
Non-Ferrous												
6061 T6 Aluminum	up to 2000	up to 1500	.0010	.0020	.0020	.0025	.0030	.0035	.0040	.0050	.0060	.0070
Copper, Brass, Bronze	up to 1200	up to 1000	.0010	.0010	.0020	.0022	.0025	.0028	.0030	.0040	.0040	.0050
Plastic	up to 2000	up to 1500	.0010	.0020	.0030	.0035	.0040	.0050	.0060	.0080	.0100	.0120

End Mill Specifications:

Cutting Diameter	+0.000/-0.002
Shank Diameter	+0.000/-0.0003
Radius	\pm .001
LOC	+0.060/-0.000
OAL	\pm .120
Neck Diameter	95% of Diam \pm .010



Metric:

Cutting Diameter	+0.000/-0.051mm
Shank Diameter	+0.000/-0.008mm
Radius	\pm 0.025mm
LOC	+1.5/-0.0mm
OAL	\pm 3.0mm
Neck Diameter	95% of Diam \pm 0.25mm

**TUNGSTEN
TOOLWORKS**.COM